

CAST IRON ARMATURE BULGARIA® SA

7800 Popovo, Industrial zone Phone: + 359 608 43654

http://www.cia.bg E-mail: cia@cia.bg




SERVICE VALVE WITH DOUBLE-SIDED INTERNAL INCH THREAD	DN	PN
SERIES 313	25-50	16

APPLICATION

The service valves are used as closing devices installed on pipelines carrying water and non-aggressive fluids with pressure PN 16 and T_{max} 70°C. The closing device is EPDM rubber drinking water. Nominal torque moment at closing-opening 50 Nm and maximum – 100 wedge. The product is certified for contact with Nm.



INSTALLATION



Normal Possible Possible Possible

MATERIALS FOR MAJOR DETAILS

No.	Detail	Material	Number	Standard	
1	Body	EN-GJS-500-7/EN-GJL-250	5.3200/5.1301	BDS EN1563/ BDS EN 1561	
2	Wedge vulcanized EPDM	CuZn35Pb2AL/EN-GJS-500-7	CC752S/5.3200	BDS EN1982/ BDS EN1563	
5	Bonnet	EN-GJS-500-7 / EN-GJL-250	5.3200/5.1301	BDS EN1563/ BDS EN 1561	
7	Bushing	CuZn40Pb2	CW617N	BDS EN 12164	
11	Stem	X20Cr13	1.4021	BDS EN 10088	
	Construction lengths	BDS EN 558-1/14/3202/F4			
	Coating	Epoxy RAL 5015			



CAST IRON ARMATURE BULGARIA® SA 7800 Popovo, Industrial zone

Phone: + 359 608 43654

http://www.cia.bg E-mail: cia@cia.bg



DIMENSIONS

Series	DN	G	L	Н
313	25	3/4"	115	172
313	25	1"	115	172
313	32	1 1⁄4"	130	187
313	40	1 ½"	150	195
313	50	2 "	180	200

